

Industrial Vibrators Direct Current

EACC Series



EACC series DC electric vibrators are designed for on-board use in vehicles and are battery-powered.

The 5 500 rpm EACC-6002 is particularly well-suited to vibrating ready-mixed concrete and preparing concrete specimens on site for laboratory testing.



Features:

- 12 V and 24 V DC power supply
- Mechanical protection: IP65-7
- Delivered wired, without plugs or bolts



Highlights:

- Battery-powered, designed for on-board use
- Suitable for truck mixers and concrete mixers

Energy : Electric

Sectors : Building and construction, Industry, Prefabrication

Applications : Compaction, Draining, Flow, Screening, Sieving, Sorting, Unclogging

Type	Frequency (rpm)	Static Moment (Kg/mm)	Centrifugal Force (Kg)	Weight (Kg)	Power (W)	Nominal current (A)	
						12 V	24V
EACC-3002	3 100	18.60	200	6.1	130	10.8	5.4
EACC-6002	5 500	5.26	178	5.8	130	10.8	5.4

Type	A	B	C	D	ØE	F	G	L	M	ØN	P	Q	R	S	Cable
EACC-3002	212	150	150	132	105	59	46	62-74 70	106 130	4 x M8	98	30	35	22	M16x1.5
EACC-6002	212	150	150	132	105	59	46	62-74 70	106 130	4 x M8	98	30	35	22	M16x1.5

Dimensions : mm

